



Vendor: Cisco

Exam Code: 300-415

**Exam Name: Implementing Cisco SD-WAN Solutions
(ENSDWI)**

Version: 13.01

Q & As: 60

QUESTION 1

Which component of the Cisco SD-WAN architecture oversees the control plane of overlay network to establish, adjust, and maintain the connections that form the Cisco SD-WAN fabric?

- A. APIC-EM
- B. vSmart
- C. vManage
- D. vBond

Correct Answer: B

Explanation:

<https://www.cisco.com/c/dam/en/us/td/docs/routers/sdwan/migration-guide/cisco-sd-wan-migration-guide.pdf>

QUESTION 2

Which two hardware platforms support Cisco IOS XE SD-WAN images? (Choose two.)

- A. ISR4000 series
- B. ISR9300 series
- C. vEdge-1000 series
- D. ASR9000 series
- E. ASR1000 series

Correct Answer: AE

Explanation:

https://www.cisco.com/c/en/us/solutions/collateral/enterprise-networks/sd-wan/white_paper-c11-741071.html

QUESTION 3

What is a default protocol for control plane connection?

- A. HTTPS
- B. TLS
- C. IPsec
- D. DTLS

Correct Answer: D

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/Software_Features/SD-WAN_Release_16.3/05Security/02Configuring_Security_Parameters

QUESTION 4

DRAG DROP

Drag and drop the devices from the left onto the correct functions on the right.

vSmart	establishes a secured data plane
vManage	first point of authentication
vEdge	single pane of glass
vBond	enforces control policies

Correct Answer:

vSmart	vEdge
vManage	vBond
vEdge	vManage
vBond	vSmart

QUESTION 5

Which component of the Cisco SD-WAN control plane architecture should be located in a public Internet address space and facilitates NAT-traversal?

- A. WAN Edge
- B. vSmart
- C. vBond
- D. vManage

Correct Answer: C

Explanation:

https://www.cisco.com/c/dam/global/da_dk/assets/pdfs/cisco_virtual_update_cisco_sdwan_viptela.pdf

QUESTION 6

Which Cisco SD-WAN WAN Edge platform supports LTE and Wi-Fi?

- A. ISR 1101
- B. ASR 1001
- C. CSR 1000v
- D. vEdge 2000

Correct Answer: A

QUESTION 7

Refer to the exhibit. What does the BFD value of 8 represent?

Hostname	State	System IP	Reachability	Site ID	Device Model	BFD	Control
BR1-VEEDGE1	✓	10.3.0.1	reachable	300	vEdge Cloud	8	5

- A. dead timer of BFD session
- B. poll-interval of BFD session
- C. hello timer of BFD session
- D. number of BFD sessions

Correct Answer: D

QUESTION 8

What are the two advantages of deploying cloud-based Cisco SD-WAN controllers? (Choose two.)

- A. centralized control and data plane
- B. infrastructure as a service
- C. management of SLA
- D. centralized raid storage of data
- E. distributed authentication policies

Correct Answer: AC

QUESTION 9

Which two image formats are supported for controller codes? (Choose two.)

- A. .nxos
- B. .qcow2
- C. .iso
- D. .ova
- E. .tgz

Correct Answer: BD

QUESTION 10

Which two platforms for the Cisco SD-WAN architecture are deployable in a hypervisor on-premises or in IAAS Cloud? (Choose two.)

- A. CSR 1000v
- B. ISR 4431
- C. vEdge 100c
- D. vEdge 2000
- E. vEdge Cloud

Correct Answer: AE

QUESTION 11