



Vendor: Cisco

Exam Code: 300-715

Exam Name: Implementing and Configuring Cisco Identity Services Engine (SISE)

Version: Demo

QUESTION 1

While configuring Cisco TrustSec on Cisco IOS devices the engineer must set the CTS device ID and password in order for the devices to authenticate with each other. However after this is complete the devices are not able to properly authenticate. What issue would cause this to happen even if the device ID and passwords are correct?

- A. The device aliases are not matching
- B. The 5GT mappings have not been defined
- C. The devices are missing the configuration `cts credentials trustsec verify 1`
- D. EAP-FAST is not enabled

Correct Answer: B

QUESTION 2

An administrator is configuring a Cisco WLC for web authentication. Which two client profiling methods are enabled by default if the Apply Cisco ISE Default Settings check box has been selected? (Choose two.)

- A. CDP
- B. DHCP
- C. HTTP
- D. SNMP
- E. LLDP

Correct Answer: AE

QUESTION 3

Which portal is used to customize the settings for a user to log in and download the compliance module?

- A. Client Profiling
- B. Client Endpoint
- C. Client Provisioning
- D. Client Guest

Correct Answer: C

QUESTION 4

An administrator is configuring sponsored guest access using Cisco ISE. Access must be restricted to the sponsor portal to ensure that only necessary employees can issue sponsored accounts and employees must be classified to do so. What must be done to accomplish this task?

- A. Configure an identity-based access list in Cisco ISE to restrict the users allowed to login
- B. Edit the sponsor portal to only accept members from the selected groups
- C. Modify the sponsor groups assigned to reflect the desired user groups
- D. Create an authorization rule using the Guest Flow condition to authorize the administrators

Correct Answer: C

QUESTION 5

An administrator enables the profiling service for Cisco ISE to use for authorization policies while in closed mode. When the endpoints connect, they receive limited access so that the profiling

probes can gather information and Cisco ISE can assign the correct profiles. They are using the default values within Cisco ISE. but the devices do not change their access due to the new profile. What is the problem'?

- A. In closed mode, profiling does not work unless CDP is enabled.
- B. The profiling probes are not able to collect enough information to change the device profile
- C. The profiler feed is not downloading new information so the profiler is inactive
- D. The default profiler configuration is set to No CoA for the reauthentication setting

Correct Answer: D

QUESTION 6

What should be considered when configuring certificates for BYOD?

- A. An endpoint certificate is mandatory for the Cisco ISE BYOD
- B. An Android endpoint uses EST whereas other operation systems use SCEP for enrollment
- C. The CN field is populated with the endpoint host name.
- D. The SAN field is populated with the end user name

Correct Answer: A

QUESTION 7

What is the purpose of the ip http server command on a switch?

- A. It enables the https server for users for web authentication
- B. It enables MAB authentication on the switch
- C. It enables the switch to redirect users for web authentication.
- D. It enables dot1x authentication on the switch.

Correct Answer: C

QUESTION 8

What must be configured on the Cisco ISE authentication policy for unknown MAC addresses/identities for successful authentication?

- A. pass
- B. reject
- C. drop
- D. continue

Correct Answer: D

QUESTION 9

Which two ports must be open between Cisco ISE and the client when you configure posture on Cisco ISE? (Choose two).

- A. TCP 8443
- B. TCP 8906

- C. TCP 443
- D. TCP 80
- E. TCP 8905

Correct Answer: AE

QUESTION 10

What are two requirements of generating a single signing in Cisco ISE by using a certificate provisioning portal, without generating a certificate request? (Choose two)

- A. Location the CSV file for the device MAC
- B. Select the certificate template
- C. Choose the hashing method
- D. Enter the common name
- E. Enter the IP address of the device

Correct Answer: BD

QUESTION 11

How is policy services node redundancy achieved in a deployment?

- A. by enabling VIP
- B. by utilizing RADIUS server list on the NAD
- C. by creating a node group
- D. by deploying both primary and secondary node

Correct Answer: C

QUESTION 12

What is the deployment mode when two Cisco ISE nodes are configured in an environment?

- A. distributed
- B. active
- C. standalone
- D. standard

Correct Answer: A

QUESTION 13

If a user reports a device lost or stolen, which portal should be used to prevent the device from accessing the network while still providing information about why the device is blocked?

- A. Client Provisioning
- B. Guest
- C. BYOD
- D. Blacklist

Correct Answer: D

QUESTION 14

Which Cisco ISE service allows an engineer to check the compliance of endpoints before

connecting to the network?

- A. personas
- B. qualys
- C. nexpose
- D. posture

Correct Answer: D

QUESTION 15

An engineer is configuring Cisco ISE for guest services. They would like to have any unregistered guests redirected to the guest portal for authentication, then have a CoA provide them with full access to the network that is segmented via firewalls. Why is the given configuration failing to accomplish this goal?

- A. The Guest Flow condition is not in the line that gives access to the guest portal.
- B. The Network_Access_Authentication_Passed condition will not work with guest services for portal access.
- C. The Permit Access result is not set to restricted access in its policy line.
- D. The Guest Portal and Guest Access policy lines are in the wrong order.

Correct Answer: D

QUESTION 16

An administrator is configuring posture with Cisco ISE and wants to check that specific services are present on the workstations that are attempting to access the network. What must be configured to accomplish this goal?

- A. Create a registry posture condition using a non-OPSWAT API version.
- B. Create an application posture condition using a OPSWAT API version.
- C. Create a compound posture condition using a OPSWAT API version.
- D. Create a service posture condition using a non-OPSWAT API version.

Correct Answer: D

QUESTION 17

An engineer is using the low-impact mode for a phased deployment of Cisco ISE and is trying to connect to the network prior to authentication. Which access will be denied in this?

- A. HTTP
- B. DNS
- C. EAP
- D. DHCP

Correct Answer: A

QUESTION 18

An administrator connects an HP printer to a dot1x enable port, but the printer is not accessible. Which feature must the administrator enable to access the printer?

- A. MAC authentication bypass
- B. change of authorization